

TRICO.PRO

Driver

Date :

Event :

Track/Nation :

Power Info.	ESC/Firmware Ver. <input type="text" value="1.2 Stock"/>	Motor <input type="text" value="TM-SMM175 TricoRoll Brushless MM 17.5T JMRCA 全日本SP"/>
	Gear Ratio <input type="text" value="5.94"/>	Motor Timing <input type="text" value="30度"/>
	Battery <input type="text" value="TB-6000SR TRION Li-Po 6000mAh Stock Spec"/>	Rotor Size <input type="text" value="TR-125BL3 (12.5 x 7.25 x 25.3mm)"/>
Track Info.	Indoor <input type="checkbox"/> Outdoor <input checked="" type="checkbox"/>	Comment & Result ローターはモータ本体 (TM-SMM175) に標準装備されています。 ファームウェアは「Stock」に書き換えています。
	On-Road <input checked="" type="checkbox"/> Off-Road <input type="checkbox"/>	
	Track Surface <input type="text" value="アスファルト"/>	
	Track Type Technical <input checked="" type="checkbox"/> Mixed <input type="checkbox"/> Fast <input type="checkbox"/>	
	Track Traction Low <input type="checkbox"/> Medium <input checked="" type="checkbox"/> High <input type="checkbox"/>	
Temp : Track <input type="text"/> / Weather <input type="text"/> (C° <input type="text"/> / F° <input type="text"/>)		

SETUP DATA	1	2	3	4	5	6	7	8	9
Operation Mode	Forward Brake <input checked="" type="checkbox"/>	For/Reverse Brake <input type="checkbox"/>	Forward Reverse <input type="checkbox"/>						
Reverse Speed	25% <input checked="" type="checkbox"/>	50% <input type="checkbox"/>	75% <input type="checkbox"/>	100% <input type="checkbox"/>					
Low Volt Cut	None <input type="checkbox"/>	2.9V/cell <input type="checkbox"/>	3.0V/cell <input checked="" type="checkbox"/>	3.2V/cell <input type="checkbox"/>	Custom(V/cell) <input type="text"/>				
Drag Brake	<input type="text" value="0"/> %								
Initial Brake	=Drag Brack <input checked="" type="checkbox"/>	<input type="text"/> %							
Full Brake	75% <input type="checkbox"/>	80% <input type="checkbox"/>	85% <input type="checkbox"/>	90% <input checked="" type="checkbox"/>	95% <input type="checkbox"/>	100% <input type="checkbox"/>			
Brake Frequency	1Khz <input type="checkbox"/>	2Khz <input checked="" type="checkbox"/>	4Khz <input type="checkbox"/>	8Khz <input type="checkbox"/>	16Khz <input type="checkbox"/>	32Khz <input type="checkbox"/>			
Power Level	Level(1-12) <input type="text" value="9"/>								
Drive Frequency	2Khz <input type="checkbox"/>	4Khz <input type="checkbox"/>	8Khz <input type="checkbox"/>	16Khz <input checked="" type="checkbox"/>	32Khz <input type="checkbox"/>	64Khz <input type="checkbox"/>			
Neutral Dead Band	0% <input type="checkbox"/>	3% <input checked="" type="checkbox"/>	6% <input type="checkbox"/>	9% <input type="checkbox"/>	12% <input type="checkbox"/>				
Temp Cut Set	Off <input checked="" type="checkbox"/>	176F/80C <input type="checkbox"/>	194F/90C <input type="checkbox"/>						
Boost Timing	<input type="text" value="43"/> Deg								
Boost RPM	<input type="text" value="1000"/> RPM								
Boost ACC	<input type="text" value="250"/> RPM/Deg								
Turbo Timing	<input type="text" value="30"/> Deg								
Turbo Slope	3Deg/0.1S <input type="checkbox"/>	6Deg/0.1S <input type="checkbox"/>	12Deg/0.1S <input type="checkbox"/>	18Deg/0.1S <input type="checkbox"/>	24Deg/0.1S <input checked="" type="checkbox"/>	Fastest <input type="checkbox"/>			
Turbo Delay	Off <input checked="" type="checkbox"/>	0.05sec <input type="checkbox"/>	0.1sec <input type="checkbox"/>	0.15sec <input type="checkbox"/>	0.2sec <input type="checkbox"/>	0.25sec <input type="checkbox"/>	0.3sec <input type="checkbox"/>	0.35sec <input type="checkbox"/>	0.4sec <input type="checkbox"/>
Rotation Mode	Normal <input checked="" type="checkbox"/>	Reverse <input type="checkbox"/>							