

# TRIGO.PRO

Driver:

Date:

Event:

Track/Nation:

Power Info.	ESC/Firmware Ver.	<input type="text" value="Blinky 1.3"/>	Motor	<input type="text" value="とりこロ〜ル M4 21.5T 全日本SP"/>
	Gear Ratio	<input type="text" value="76T / 49T (指数85前後)"/>	Motor Timing	<input type="text" value="一番右から3コマ目"/>
	Battery	<input type="text" value="TRION Li-Po Battery 3500mAh/7.4V/90C"/>	Rotor Size	<input type="text" value="トルク型 13mm"/>
Track Info.	Indoor	<input checked="" type="checkbox"/>	Outdoor	<input type="checkbox"/>
	On-Road	<input checked="" type="checkbox"/>	Off-Road	<input type="checkbox"/>
	Track Surface	<input type="text" value="カーペット"/>		
	Track Type	Technical <input type="checkbox"/>	Mixed <input checked="" type="checkbox"/>	Fast <input type="checkbox"/>
	Track Traction	Low <input type="checkbox"/>	Medium <input checked="" type="checkbox"/>	High <input type="checkbox"/>
	Temp : Track	<input type="text"/>	/ Weather	<input type="text"/>
				<b>Comment &amp; Result</b> グリップが確保できたら、ローターはトルク型13.5mmもアリです。 その場合、指数は+3くらいしてください。

SETUP DATA	1	2	3	4	5	6	7	8	9
Operation Mode	Forward Brake <input checked="" type="checkbox"/>	For/Reverse Brake <input type="checkbox"/>	Forward Reverse <input type="checkbox"/>						
Reverse Speed	25% <input checked="" type="checkbox"/>	50% <input type="checkbox"/>	75% <input type="checkbox"/>	100% <input type="checkbox"/>					
Low Volt Cut	None <input type="checkbox"/>	2.9V/cell <input type="checkbox"/>	3.0V/cell <input checked="" type="checkbox"/>	3.2V/cell <input type="checkbox"/>	Custom(V/cell) <input type="text"/>				
Drag Brake	<input type="text" value="0"/> %								
Initial Brake	=Drag Brack <input checked="" type="checkbox"/>	<input type="text"/> <input type="text"/> %							
Full Brake	75% <input type="checkbox"/>	80% <input checked="" type="checkbox"/>	85% <input type="checkbox"/>	90% <input type="checkbox"/>	95% <input type="checkbox"/>	100% <input type="checkbox"/>			
Brake Frequency	1Khz <input type="checkbox"/>	2Khz <input type="checkbox"/>	4Khz <input type="checkbox"/>	8Khz <input checked="" type="checkbox"/>	16Khz <input type="checkbox"/>	32Khz <input type="checkbox"/>			
Power Level	Level(1-12) <input type="text" value="6"/>								
Drive Frequency	2Khz <input type="checkbox"/>	4Khz <input type="checkbox"/>	8Khz <input checked="" type="checkbox"/>	16Khz <input type="checkbox"/>	32Khz <input type="checkbox"/>	64Khz <input type="checkbox"/>			
Neutral Dead Band	0% <input type="checkbox"/>	3% <input checked="" type="checkbox"/>	6% <input type="checkbox"/>	9% <input type="checkbox"/>	12% <input type="checkbox"/>				
Temp Cut Set	Off <input checked="" type="checkbox"/>	176F/80C <input type="checkbox"/>	194F/90C <input type="checkbox"/>						
Boost Timing	<input type="text"/> Deg								
Boost RPM	<input type="text"/> RPM								
Boost ACC	<input type="text"/> RPM/Deg								
Turbo Timing	<input type="text"/> Deg								
Turbo Slope	3Deg/0.1S <input type="checkbox"/>	6Deg/0.1S <input type="checkbox"/>	12Deg/0.1S <input type="checkbox"/>	18Deg/0.1S <input type="checkbox"/>	24Deg/0.1S <input type="checkbox"/>	Fastest <input type="checkbox"/>			
Turbo Delay	Off <input type="checkbox"/>	0.05sec <input type="checkbox"/>	0.1sec <input type="checkbox"/>	0.15sec <input type="checkbox"/>	0.2sec <input type="checkbox"/>	0.25sec <input type="checkbox"/>	0.3sec <input type="checkbox"/>	0.35sec <input type="checkbox"/>	0.4sec <input type="checkbox"/>
Rotation Mode	Normal <input type="checkbox"/>	Reverse <input type="checkbox"/>							